



**TDS12503**

**Mini Remote Control**

The TDS12503 is a small and user friendly infra-red remote control for home automation control. The controlled functions adapt automatically according the touch panel or interface to which the infrared remote control is communicating (button 1 controls function 1 of the TELETASK interface which receives the IR code).

**APPLICATION**

To be used where remote control of the functions on a touch panel or other TELETASK interface with infrared receiver is desired.

There are more functions to be controllable on the remote control than on a touch panel or digital input interface.

To be used in combination with an IR receiver (in touch panel or external with TDS12125).

**CHARACTERISTICS**

The remote control is equipped with 8 buttons for the control of 8 functions; the controlled function depends on the TELETASK interface that receives the IR command.

If the 'TELETASK button' is pressed in combination with the 8 numeric buttons, it will control the 8 "MASTER" functions.

**Battery**

CR2025 (3V Lithium) – supplied with the unit. Compatible with CR2032

**SETTINGS**

IR functions via PROSOFT

**POWER CONSUMPTION**

Estimated battery lifetime: 1 year (no warranty on the battery)

**DIMENSIONS**

35 W x 135 H x 11 D (mm)

**NET | GROSS WEIGHT**

0,015 kg | 0,050 kg

**PACKAGING CONTENT**

TDS12503 + battery

**ENVIRONMENTAL CONDITIONS**

**Storage (with no condensation or icing)**

Temperature: -20°C to +65°C max.

Relative humidity: 5% to 85% max.

**Operation (with no condensation or icing)**

Temperature: 0°C to +50°C max.

Relative humidity: 5% to 80% max.

**IP PROTECTION RATE**

IP20