



TDS56409G3

DOMUS Demo case

This portable demo case is intended to be used for:

- Practicing the configuration of a TELETASK System.
- Basic training about cabling and connecting.
- Commercial demo of lighting (switch/dim), wall sockets, sun blinds, heating/cooling, scenes, etc... including wireless GUI's (ATMOS and GUI+) on PC, tablet & smartphone. Optional very useful for voice control demo (voice control unit not included).
- Exercises and demo of the integration of IP camera's on the GUI's
- Built-in Wi-Fi / 4G router + IP-camera.

The 4G option of the router can be provided with a SIM card (not included) in the absence of a wired internet connection. The case contains a graphical demo house with buttons, LED's, DOMUS central unit, AURUS-OLED, AURUS-2 SENSE, remote control, ... The mains cord is the only connection you have to make for a complete PROSOFT and GUI demo.

APPLICATION

Training, demo, programming practice.

CHARACTERISTICS

Mechanical

Ruggedized case with DOMUS central unit and AURUS panels.

Electrical

Plug-in connector for 100-240VAC power cord.

Content

TDS10309	DOMUS Central Unit
TDS10132	AUTOBUS Power supply
TDS12022BL	AURUS-OLED
TDS12025BL	AURUS-2 SENSE
TDS12503	IR Remote control
TSF16103	3 years ATMOS Subscription
TDS15105	GUI+ License
TDS15240	A/V License
(4G) WiFi Router (SIM-card not included)	
IP-camera	

INSTALLATION

Carry case – Ready to use.

CONNECTIONS

Electrical

Plug-in connector for 110/230V power supply cord.

LAN

(4G) WIFI router on board.

DIMENSIONS

600 x 400 x 223 mm

NET | GROSS WEIGHT

8,1 | 8,4 kg

STORAGE

Temperature

-20°C to +65°C

Relative humidity

15% to 85%

IP PROTECTION RATE

IP20


OPERATING RANGE

Temperature

0°C to +50°C max.

Relative humidity

5% to 80% at 25°C (non-condensing ambient)



SCHEMATIC DRAWING

